
















Amtico Entryway

Teknisk Specifikation

ENT-TS-20160901-02-SE

Namn	Kollektion	Standard	Symbol	Resultat
Bruksklassificering	Ruffian, Recoarse & Take Back	EN 1307		33
Komfortklass	Ruffian	EN 1307		LC3
	Recoarse & Take Back			LC4
Total Vikt	Ruffian	ISO 8543		5 700 g/m ²
	Recoarse			5 300 g/m ²
	Take Back			5 400 g/m ²
Total Tjocklek	Ruffian & Take Back	ISO 1765		8,9 mm
	Recoarse			8,7 mm
Luggtyp	Ruffian & Take Back	EN 1307		Tip-sheated loop
	Recoarse			Textured patterned loop
Ytdesign	Ruffian, Recoarse & Take Back	EN 1307		Flerfärgad
Luggmaterial	Ruffian	EN 1307		nylon 6,6 / solution dyed
	Recoarse			nylon 6,6 / solution dyed
	Take Back			nylon 6,6 / piece dyed
Luggvikt	Ruffian	ISO 8543		650 g/m ²
	Recoarse			900 g/m ²
	Take Back			1 000 g/m ²
Luggtjocklek	Ruffian	ISO 1766		4,2 mm
	Recoarse			5,1 mm
	Take Back			5,4 mm
Luggdensitet	Ruffian	ISO 8543		0,157 g/cm ³
	Recoarse			0,180 g/cm ³
	Take Back			0,185 g/cm ³
Antal tufter	Ruffian	ISO 1763		85 000/m ²
	Recoarse			195 000/m ²
	Take Back			250 000/m ²
Tuftstomme	Ruffian, Recoarse & Take Back	EN 1307		Vävd Polyester
Backing	Ruffian, Recoarse & Take Back	EN 1307		Vinyl
Lämplig för trappor	Ruffian, Recoarse & Take Back	EN 1307		Ja (med trappnos)
Brandklass	Ruffian, Recoarse & Take Back	EN 13501-1		C _{FL} - S1
Stegsäkerhet	Ruffian, Recoarse & Take Back	EN 13893		Class DS
Kulörbeständighet / Ljus	Ruffian, Recoarse & Take Back	EN ISO 105 B02		≥ 6
Kulörbeständighet / Mekanisk Gnidning	Ruffian, Recoarse & Take Back	EN ISO 105 X12		4-5
Kulörbeständighet vatten	Ruffian, Recoarse & Take Back	EN ISO 105 E01		4-5
Vertikal Elektrisk resistans	Ruffian, Recoarse & Take Back	ISO 10965		≤ 10 ¹⁰ Ω
Statisk personuppladdning	Ruffian, Recoarse & Take Back	ISO 6356		≤ 2 kV
Dimensionsstabilitet	Ruffian, Recoarse & Take Back	EN 986		≤ 0,1%
Tålighet mot kantfransning	Ruffian, Recoarse & Take Back	EN1814		Godkänd