























Amtico Signature Acoustic

Technical Specifications

ASIG-TS-20201208-07-EN

Name	Standard	Symbol	Result
CE / DOP	EN 14041		CPR/AI/010
Usage Classification	EN ISO 10874		34, 42
Manufacturing Standard	EN 651		Pass
Total Thickness	EN ISO 24346		3,5 mm
Wear Layer Thickness	EN ISO 24340		1,0 mm
Acoustic Layer Thickness	EN ISO 24340		1,0 mm
Weight	EN ISO 23997		3,350 g/m ²
Dimensional Stability	EN ISO 23999		≤ 0,25%
Dimensional Stability / Curling	EN ISO 23999		Pass
Residual Indentation	EN ISO 24343-1		≤ 0,20 mm
Abrasion Resistance	EN 651		Group T
Light Stability	EN ISO 105-B02		6 or better
Chemical Resistance	EN ISO 26987		Excellent
Castor Chair Resistance (Type W)	EN ISO 4918		Pass
Furniture Leg Resistance (Type 0, 2, 3)	EN ISO 16581		Pass
Electrostatic Performance	EN 1815		≤ 2kV
Flammability / Smoke Emissions	EN 13501-1		B _{fl} -s1
Sound Reduction	EN ISO 717-2		18 dB
Thermal Resistance	EN ISO 12664		0,040 m ² K/W (suitable for underfloor heating)
Emissions	IAC Gold		Certificate no. IACG-352-01-12-2020
Emissions	M1		Certified / https://cer.rts.fi/en/m1
Environment	BRE Green Guide		Comparable to Green Guide generic elements 821570010, 821570041 and 821570053, rated as A+/A
Emissions COV		 information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).	A+
Slip Resistance	DIN 51130 EN 13893		R10* Class DS
Surface Treatment			Urethane (Quantum Guard Elite)
Phthalate Free		 Amtico Signature Acoustic products are manufactured using both phthalate free and biobased plasticisers.	Yes

* For Safety flooring with long-term retention of slip resistance we refer to the Sinature 36+ /Spacia 36+ collections.

Amtico International Head Office +44 (0) 24 7686 1400
Kingfield Road, Coventry
CV6 5AA, UK info@amtico.com
amtico.com

amtico
flooring