

Amtico Spacia 36+

Technical Specification

SPA36-TS-20210719-04-EN

Name	Standard	Symbol	Result
CE / DOP	EN 14041		CPR/AI/017
Usage Classification	EN ISO 10874		34, 43
Manufacturing Standard	EN 13845		Pass
Total Thickness	EN ISO 24346		2.5 mm
Wear Layer Thickness	EN ISO 24340		0.55 mm
Weight	EN ISO 23997		3600 g/m ²
Dimensional Stability	EN ISO 23999		≤ 0.25%
Dimensional Stability / Curling	EN ISO 23999		≤ 2 mm
Residual Indentation	EN ISO 24343-1		≤ 0.1 mm
Flexibility	EN ISO 24344 Method A		Pass
Abrasion Resistance	EN ISO 10582		Type 1
Light Stability	EN ISO 105-B02		6 or better
Chemical Resistance	EN ISO 26987		Excellent
Castor Chair Resistance (Type W)	EN ISO 4918		Pass
Flammability / Smoke Emissions	EN 13501-1		B _{fl} -s1
Impact Sound Reduction	EN ISO 717-2		5 dB
Thermal Resistance	EN ISO 12664		0.017 m ² K/W (underfloor heating suitable)
Surface Treatment			Quantum Guard Urethane Coating
Phthalate Free		Amtico Spacia 36+ products are manufactured using both phthalate free and biobased plasticisers.	Yes
Emissions	IAC Gold		Certificate no. IACG-352-01-02-2020
Environment	BRE Green Guide		Comparable to Green Guide generic elements 821570055, 821570043 and 921570010 rated as A+/A/B respectively
Emissions	French VOC regulation	Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).	Pass Pass A+
Slip Resistance	EN 13893 DIN 51130 BS 7976		Class DS R10* >36 wet
Slip Classification Class ESf (Footwear)	EN 13845 Annex C		Pass
Resistance to Wear	EN 13845 Annex D		34, 43
Antimicrobial Activity	ISO 22196:2011	Amtico Spacia 36+ is manufactured incorporating an antimicrobial additive from SteriTouch® -Tested against MRSA, E-coli, VRE & CPE.	≥ 99.99% Reduction

* Meets safety flooring criteria with long-term retention of slip resistance

Amtico International Head Office +44 (0) 24 7686 1400
Kingfield Road, Coventry info@amtico.com
CV6 5AA, UK amtico.com

amtico
flooring